

# NEXTIMO LED 140 – HV



**10-YEAR WARRANTY**  
lack of electrolytic capacitors

## TECHNICAL SPECIFICATION:

<b>Luminous flux</b>	22 237 lm*
<b>Energy consumption</b>	149,9W - 170W
<b>Light source</b>	XTE CREE LEDs (USA)
<b>Optics</b>	S0, S60
<b>Colour temperature</b>	4000 - 4700 K
<b>Power</b>	200 - 265V AC
<b>Power Factor (PF)</b>	0,99
<b>Board material</b>	MPCB (aluminium)
<b>Protection class</b>	IP64
<b>Product weight</b>	7 kg
<b>Housing material</b>	anodized aluminium
<b>Lamp cover</b>	tempered glass (safety)

\* based on the LED manufacturer's data


## BENEFITS

- Fail-safe
- High-performance light
- No UV and IR emission
- LM-80 (TM-21) report


## CHARACTERISTIC:

- Product is protected by patent law
- The highest quality selected CREE LEDs (USA)
- SELF-COOLING - anodized aluminum housing, Improves heat dissipation.
- Modern design with handles for easy installation in line or stand-alone
- Made in Poland
- Designed for industrial halls, manufacturing plants, distribution centers, warehouses, etc.

S0 optics



S60 optics



<b>Lifetime:</b>	L90 > 45 600 h
	L80 > 88 500 h
	L70 > 110 000 h

